



Corrugated Split Sleeve Tubing



*Denotes Retail Packs

Part No.	Length Per Bag/Spool (metres)	Description	Internal Diameter (mm)
NA56707-3*	3	Manufactured of black U.V. resistant, fire-retardant polypropylene. Operating temperature -25C to +110C	7mm
NA56707	10	As Above	7mm
NA56708	30	As Above	7mm
NA56709	200	As Above	7mm
NA56710-3*	3	As Above	10mm
NA56710	10	As Above	10mm
NA56711	30	As Above	10mm
NA56712	125	As Above	10mm
NA56713-3*	3	As Above	13mm
NA56713	10	As Above	13mm
NA56714	30	As Above	13mm
NA56715	75	As Above	13mm
NA56716-3*	3	As Above	16mm
NA56716	10	As Above	16mm
NA56717	30	As Above	16mm
NA56718	50	As Above	16mm
NA56720	10	As Above	20mm
NA56721	30	Manufactured of black U.V. resistant, fire-retardant polypropylene. Operating temperature -25C to +110C	20mm
NA56722	50	As Above	20mm
NA56723	5	As Above	23mm
NA56724	30	As Above	23mm
NA56725	50	As Above	23mm
NA56729	3	As Above	29mm
NA56730	10	As Above	29mm
NA56731	40	As Above	29mm